

SUBWOOFERS

FLATBOY SLIM

▸ Device Type	
	Passive bandpass flat subwoofer
▸ Technical Data	
Woofer	5,5" Flat bass speaker
Frequency Range	45–200 Hz
Crossover Frequency	40–150 Hz
Power Consumption	30 W RMS
▸ Connections	
Input	RIA AKL 22004 (+ - + -)
▸ Housing	
Material	HDF housing with textured paint, anodized aluminium cover plate
Color	Black, White
Width	270 mm
Height	58 mm
Depth	410 mm
Weight	2 kg

FLATBOY SLIM-WP WATERPROOF

▸ Flatboy Slim is also available in a waterproof version, certified to IP65 standard, ensuring reliable performance in demanding outdoor environments.



PAUL 12.1

▸ Device Type

	12“ high power handling and low distortion compact sub-woofer for install

▸ Technical Data

Woofer	1 x 12“ carbon fiber cone and dustcap
Transmission Range	30–200 Hz (-6 dB)
Max. SPL 1M	125 dB
Impedance	8 Ohm
Power Consumption	1000 W AES

▸ Connections

Input	SpeakON

▸ Housing

Material	Birch multiplex with polyurea coating
Color	Blacks
Width	430 mm
Height	430 mm
Depth	450 mm
Weight	26 kg

PAUL 12.1-WP WATERPROOF

▸ Paul 12.1 is also available in a waterproof version, certified to IP65 standard, ensuring reliable performance in demanding outdoor environments.



Engineered and produced in Germany.

LARS 8.1

▸ Device Type

	8“ high power handling and low distortion compact subwoofer for install

▸ Technical Data

Woofer	1 x 8“ carbon fiber cone and dustcap
Transmission Range	35–200 Hz (-6 dB)
Max. SPL 1M	106 dB
Impedance	8 Ohm
Power Consumption	200 W AES

▸ Connections

Input	SpeakON

▸ Housing

Material	50 mm birch multiplex with polyurea coating
Color	Black
Width	260 mm
Height	435 mm
Depth	390 mm
Weight	10 kg
Suspension	2 x M8 thread

LARS 8.1-WP WATERPROOF

▸ Lars 8.1 is also available in a waterproof version, certified to IP65 standard, ensuring reliable performance in demanding outdoor environments.



Engineered and produced in Germany.